

P1234, Diagnostic information

Technical data

"Solenoid valve, pump unit (B131, B132, B133, B134, B135, B136)"

Location of component(s)

"Location information, PMCI-2"

Electrical diagram(s)

"PMCI-2"

Description of component(s)

"Solenoid valve, pump unit (B131, B132, B133, B134, B135, B136)"

Block diagram

"PMCI-2"

Step by step troubleshooting



Please perform the troubleshooting steps below by utilizing the breakout harness if necessary to check electrical components such as sensors, electrical control units or harnesses. Back probing is not recommended as it could damage the harness. The ignition should always be in the OFF position when connecting or disconnecting electrical components to reduce the likelihood of damage to electrical components.



- This troubleshooting tree is based on the assumption that supply power and ground to the PMCI is functioning properly.
- Disconnecting the PMCI connectors during the troubleshooting process will result in multiple errors.
- For specific electrical component information and pin out locations, always refer to the technical data in Rapido.
- It is necessary to exit the **'active errors'** screen in DAVIE and run the diagnostic test again to identify a change in errors.
- Remember that the truck's operational or mechanical issues may be the root cause of both active and inactive codes. Refer to the **'possible causes'** section in Rapido.

This pump unit circuit test procedure will address the following types of pump unit error:

- Short circuit across pump unit
- Pump unit open circuit
- Pump unit low side short circuit to ground
- Pump unit low side short circuit to battery voltage



Following each step, the connector removed for testing **MUST** be reconnected before proceeding to the next test.

Step 1

Visual inspection- Visually inspect all applicable connectors and harnesses for corrosion, damage

and rubbing during each step of the diagnostic procedure. Proceed to step 2.

Step 2

With key **OFF**, disconnect the pump unit connector. Turn the key **ON** and measure the voltage between the signal circuit terminal on the connector and a battery ground:

- **If the measured voltage is approximately 7.0 V** – Proceed to step 3.
- **If the measured voltage is below 5.0 V or above 9.0 V**– Proceed to step 5.

Step 3

With key **OFF**, disconnect the pump unit connector and perform a diode check between the connector ground circuit terminal and battery ground. Please refer to your multimeter operation manual for the correct diode check procedure:

- **If the circuit is open during the REVERSE bias test and measures $600\text{ mV} \pm 200\text{ mV}$ during the FORWARD bias test** – Replace the pump unit. Proceed to the verification procedure listed at the end of this document.
- **If any result other than open circuit during the REVERSE bias test and $600\text{ mV} \pm 200\text{ mV}$ during the FORWARD bias test is found** - Proceed to step 4.

Step 4

With key **OFF**, disconnect the encapsulated harness at the PMCI and perform a diode check between the ground circuit terminal on the PMCI and battery ground. Please refer to your multimeter operation manual for the correct diode check procedure:

- **If the circuit is open during the REVERSE bias test and measures $600\text{ mV} \pm 200\text{ mV}$ during the FORWARD bias test** – Replace the encapsulated harness. Proceed to the verification procedure listed at the end of this document.
- **If any result other than open circuit during the REVERSE bias test and $600\text{ mV} \pm 200\text{ mV}$ during the FORWARD bias test is found** - Proceed to step 6.

Step 5

Disconnect the encapsulated harness from the PMCI. Turn the key **ON** and measure the voltage between the signal circuit terminal on the PMCI and battery ground:

- **If the measured voltage is approximately 7.0 V** – Replace the encapsulated harness. Proceed to the verification procedure listed at the end of this document.
- **If the measured voltage is below 5.0 V or above 9.0 V** - Proceed to step 6.

Step 6

Possible PMCI failure - Contact the Engine Support Center for further instruction on replacement of the PMCI.

Verification procedure

With DAVIE connected and key **ON**, clear the errors. Start the engine and let it idle to verify with DAVIE that the errors do not re-occur

M046452 - 22/07/2015

This information applies exclusively to the entered chassis number or the selected vehicle series. Please take into account that this information may change daily. Therefore the provided information is only valid on 4-10-2021. You cannot derive any rights from the information provided with respect to vehicles and/or components of another series, with another chassis number and/or of another date